

26 July, 2019



Harvest Scientific Services
Environmental and Earth Science Consultants

Mr M Collins
Collins Construction Materials Pty Ltd
214 MacArthur Road
Elderslie NSW 2570

Dear Matt,

Re: Environmental Monitoring – Spring Farm: Report 2019-7

Our Ref: 201019

This is to confirm that groundwater sampling and dust monitoring at Spring Farm (see Appendix 1 for sample locations) has been carried out with the results summarised in Tables 1 and 2 respectively below.

(a) Groundwater Monitoring

TABLE 1: SUMMARY OF GROUNDWATER MONITORING RESULTS.					
ANALYTE	VALUE	TARGET	DATE	TIME	TEMP
EC (uS/cm)	288 (<i>Non-Saline</i>)	< 800 uS/cm	27-6-2019	9.00 am	10°C
pH	5.85 (<i>Moderately acidic</i>)	4 – 6.50			
Depth to Water Table (m) ¹	11.70	> 10 m			

Notes: 1. This value represents the depth to groundwater from the TOP OF THE STAND PIPE (670 mm above ground level); 2. Refer to **Appendix 2** for laboratory analysis results and monthly summary data 3 Refer to **Appendix 3** for quality control documentation.

The results indicate that groundwater is:

- *Non-saline* and is well below the nominated target of < 800uS/cm;
- *Moderately acidic* and falling within the nominated pH range of 4 – 6.50;
- At the limit of the target depth > 10 m.

(b) Dust Monitoring

TABLE 2: SUMMARY OF DUST DEPOSITION MONITORING RESULTS.					
SAMPLING PERIOD	LOCATION	TOTAL INSOLUBLE MATTER ¹ (G/M2/MONTH)	Ash or Mineral Content (g/m2/month)	COMMENT	EMP targets (Ash or Mineral Content)
JUNE 2019	1	0.7	NT	Pass	≤ 4g / m2 per month
	2	1.3	NT	Pass	
	3	1.1	NT	Pass	

Notes: 1.Refer to **Appendix 1** for monitoring locations. 2. Refer to **Appendix 2** for laboratory analysis results and monthly summary data. Refer to **Appendix 3** for quality control documentation.

Values at monitoring stations 1, 2 and 3 all met the EMP target level.

Yours faithfully,

Mart Rampe BSc (Applied Geology)
Principal Consultant

All Correspondence to: PO Box 427 Narellan NSW 2567
Unit 4A, 20 Somerset Avenue Narellan NSW 2567
www.harvestservices.com.au
Email: office@harvestservices.com.au
Tel: 02 4647 6177 • Mobile: 0408 677 709

APPENDIX 1: Collins Spring Farm Monitoring Locations

MS 1: Dust MS 2: Dust MS 3: Dust

GW-1: Groundwater



APPENDIX 2: Laboratory Analytical Results and monthly summary data

CERTIFICATE OF ANALYSIS

Work Order : **ES1919917**
Client : **HARVEST SCIENTIFIC SERVICES**
Contact : MR MART RAMPE
Address : PO BOX 427
 NARELLAN NSW, AUSTRALIA 2567
Telephone : +61 02 4647 6177
Project : COLLINS SPRING FARM
Order number : 2019-7
C-O-C number : ----
Sampler : MR
Site : ----
Quote number : EN/222
No. of samples received : 1
No. of samples analysed : 1

Page : 1 of 2
Laboratory : Environmental Division Sydney
Contact : Customer Services ES
Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

Telephone : +61-2-8784 8555
Date Samples Received : 27-Jun-2019 12:40
Date Analysis Commenced : 28-Jun-2019
Issue Date : 30-Jun-2019 14:13



Accreditation No. 825
 Accredited for compliance with
 ISO/IEC 17025 - Testing

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Ashesh Patel	Senior Chemist	Sydney Inorganics, Smithfield, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
 LOR = Limit of reporting
 ^ = This result is computed from individual analyte detections at or above the level of reporting
 ø = ALS is not NATA accredited for these tests.
 ~ = Indicates an estimated value.

Analytical Results

Sub-Matrix: **WATER**
 (Matrix: **WATER**)

Client sample ID

				COLLINS GW-1	----	----	----	----
Client sampling date / time				27-Jun-2019 08:00	----	----	----	----
Compound	CAS Number	LOR	Unit	ES1919917-001	-----	-----	-----	-----
Result					----	----	----	----
EA005P: pH by PC Titrator								
pH Value	----	0.01	pH Unit	5.85	----	----	----	----
EA010P: Conductivity by PC Titrator								
Electrical Conductivity @ 25°C	----	1	µS/cm	288	----	----	----	----

GROUNDWATER MONITORING STATION GW-1: COLLINS SITE 2009 - 2015						
Date	Time	Temp. (°C)	EC (uS/cm)	pH	Depth to Water Table (m) from top of stand pipe	Comments
10-03-09	15:30	N/A	528	< 6.2	11.59	pH was measured using a QUIKCHEK pH test strip.
01-04-09	11:00	N/A	533	< 6.2	11.50	pH was measured using a Eutech pH 5+ meter
01-05-09	10:35	N/A	533	< 6.2	11.50	
01-06-09	10:25	17.3	541	4.79	11.50	
24-06-09	10:20	17	542	4.53	11.50	
31-07-09	9:05	17.3	598	4.98	11.59	
31-08-09	9:07	17.6	610	4.81	11.60	
30-09-09	9:45	18	619	4.71	11.59	
30-10-09	9:45	18.5	621	4.75	11.47	
27-11-09	8:00	19	~	4.73	11.47	
04-01-10	9:50	18.5	634	4.73	11.51	
02-02-10	9:45	18.7	641	4.78	11.52	
01-03-10	9:50	18.1	635	4.67	11.56	
31-03-10	9:15	18.2	639	4.74	11.56	
30-04-10	9:15	17.8	640	4.76	11.56	
01-06-10	10:40	18.1	640	4.66	11.56	
30-06-10	9:30	16.4	614	5.17	11.56	
02-08-10	10:40	17.4	639	4.64	11.56	
01-09-10	9:30	18.6	641	4.82	11.56	
05-10-10	15:50	19.3	651	4.61	11.56	
05-11-10	15:30	18.5	657	5.12	11.36	
07-12-10	9:50	19	670	5.09	11.32	
23-12-10	12:30	19.5	952	5.12	11.32	
01-02-11	12:00	20.3	657	5.17	11.39	
01-04-11	11:00	18.7	778	5.01	11.39	
29-04-11	11:30	18.3	745	5.12	11.39	
30-05-11	10:30	17	777	5.64	11.39	
01-07-11	16:30	16.5	763	5.27	11.39	
29-07-11	15:30	18.5	775	~	11.29	
01-09-11	15:30	18.8	851	4.64	11.29	
04-10-11	13:00	18.4	847	4.66	11.29	
28-10-11	15:30	19.5	846	4.48	11.29	
01-12-11	8:30	17.9	896	4.51	11.35	
23-12-11	9:45	18.8	793	4.49	11.35	
01-02-12	16:15	18.9	782	4.48	11.35	
28-02-12	8:30	18.7	806	4.42	11.35	
30-03-12	15:30	19.7	775	4.52	10.77	
30-04-12	14:30	18.9	772	4.59	10.77	
31-05-12	12:30	19	744	4.55	10.78	
08-07-12	10:30	17.5	784	4.46	10.90	
02-08-12	8:00	13.2	769	4.53	11.05	
03-09-12	15:30	19.3	759	4.66	11.20	
29-09-12	15:00	19.2	799	4.67	11.47	
01-11-12	15:00	19.8	786	4.67	11.30	
03-12-12	13:00	19.1	769	4.81	11.69	
28-12-12	14:30	19.1	767	4.69	11.69	
31-01-13	11:30	19.2	789	4.82	11.40	Prolonged period of heavy rain.
04-03-13	9:30	19.1	757	4.78	11.09	
03-04-13	N/A	N/A	756	5.24	11.21	New site personnel (Simon Winter).
03-05-13	9:30	N/A	620	4.40	11.17	Commenced laboratory analysis of pH and EC
03-06-13	15:05	N/A	670	4.80	11.20	
03-07-13	15:00	N/A	690	4.30	10.85	
02-08-13	15:00	N/A	700	5.10	10.80	
03-09-13	14:30	23	700	4.40	11.05	
03-10-13	12:05	16	680	4.40	11.15	
04-11-13	11:25	18	640	4.80	11.35	
03-12-13	10:30	23	690	4.70	11.28	
09-01-14	14:00	19	670	4.80	11.49	
04-02-14	9:45	24	680	4.60	11.49	
07-03-14	9:55	21	545	4.60	11.50	
04-04-14	10:05	20	700	4.90	11.37	
06-05-14	10:00	16	690	4.80	11.37	
03-06-14	12:15	18	652	5.26	11.47	
02-07-14	11:45	17	688	5.54	11.55	
06-08-14	11:45	20	648	5.94	11.60	New site personnel (Cheyne Hudson).
09-09-14	11:45	21	636	5.30	11.30	Commenced laboratory analysis of pH and EC at ALSE
08-10-14	11:30	20	628	5.40	11.45	
13-11-14	11:30	22	609	5.74	11.50	
03-12-14	12:00	30	598	5.84	11.50	
09-01-15	12:00	30	601	5.68	11.45	
11-02-15	11:45	28	588	5.43	11.45	
10-03-15	12:00	22	581	5.79	11.45	
08-04-15	11:00	20	573	5.13	11.40	
07-05-15	11:00	20	527	5.26	11.20	Sampling undertaken by M Rampe
10-06-15	9:00	15	507	5.28	11.20	
06-07-15	10:00	10	500	4.96	11.20	
07-08-15	10:00	12	480	5.58	11.45	
03-09-15	9:00	11	417	5.75	11.25	
08-10-15	9:00	16	423	5.15	11.50	
06-11-15	9:00	22	456	5.26	11.45	
07-12-15	10:00	23	434	5.25	11.50	

GROUNDWATER MONITORING STATION GW-1: COLLINS SITE 2016 - 2019						
Date	Time	Temp. (°C)	EC (uS/cm)	pH	Depth to Water Table (m) from top of stand pipe	Comments
04-01-16	11:00	20	409	5.00	11.50	
05-02-16	10:45	22	410	5.61	11.60	
03-03-16	9:00	23	399	5.23	11.60	
06-04-16	9:00	23	359	5.03	11.40	
05-05-16	12:30	22	363	5.77	11.50	
03-06-16	2:00	18	377	5.47	11.60	
04-07-16	12:30	13	372	5.32	10.70	
03-08-16	10:00	12	261	6.84	10.70	
05-09-16	10:00	12	250	5.62	10.40	
01-10-16	10:00	12	252	6.16	10.50	
01-11-16	8:00	11	296	5.93	10.70	
01-12-16	8:00	12	352	5.63	10.70	
06-01-17	11:00	21	363	5.45	10.70	
03-02-17	8:30	22	334	5.53	11.10	
03-03-17	8:30	23	361	5.25	11.10	
04-04-17	8:30	16	392	5.46	10.80	
01-05-17	10:30	16	294	6.09	10.70	
01-06-17	8:00	8	373	5.12	11.00	
03-07-17	8:00	2	356	5.63	10.90	
01-08-17	9:00	12	346	6.00	11.00	
04-09-17	9:00	12	352	5.63	11.00	
10-10-17	8:00	16	349	5.57	11.10	
06-11-17	9:00	16	326	5.06	11.00	
05-12-17	9:00	18	304	5.42	11.20	
11-01-18	9:00	22	305	5.72	11.10	
07-02-18	10:00	25	303	4.94	11.40	
07-03-18	9:00	20	302	4.86	11.40	
06-04-18	10:00	22	318	5.43	11.40	
03-05-18	10:00	12	307	5.37	11.50	
05-06-18	10:00	14	304	5.60	11.60	
06-07-18	10:00	20	306	5.61	11.50	
02-08-18	9:00	15	303	5.95	11.50	
03-09-18	10:00	6	311	5.57	11.60	
03-10-18	10:00	14	338	6.24	11.60	
05-11-18	10:00	20	324	6.25	11.60	
03-12-18	8:30	20	324	6.09	11.60	
11-01-19	10:00	23	291	6.07	11.50	
04-02-19	8:00	22	264	5.72	11.50	
05-03-19	10:00	25	262	5.60	11.60	
01-04-19	10:00	18	273	5.62	11.60	
01-05-19	10:00	17	221	5.81	11.60	
31-05-19	10:00	9	293	5.28	11.70	
27-06-19	9	10	288	5.85	11.70	

CERTIFICATE OF ANALYSIS

Work Order : **EN1904441**
Client : **HARVEST SCIENTIFIC SERVICES**
Contact : MR MART RAMPE
Address : PO BOX 427
 NARELLAN NSW, AUSTRALIA 2567
Telephone : +61 02 4647 6177
Project : COLLINS SPRING FARM
Order number : 2019-7
C-O-C number : ----
Sampler : MR
Site : ----
Quote number : EN/222
No. of samples received : 3
No. of samples analysed : 3

Page : 1 of 2
Laboratory : Environmental Division Newcastle
Contact :
Address : 5/585 Maitland Road Mayfield West NSW Australia 2304

Telephone : +61 2 4014 2500
Date Samples Received : 27-Jun-2019 17:15
Date Analysis Commenced : 01-Jul-2019
Issue Date : 05-Jul-2019 21:28



Accreditation No. 825
 Accredited for compliance with
 ISO/IEC 17025 - Testing

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories	Position	Accreditation Category
Dianne Blane	Laboratory Coordinator (2IC)	Newcastle - Inorganics, Mayfield West, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
 LOR = Limit of reporting
 ^ = This result is computed from individual analyte detections at or above the level of reporting
 ø = ALS is not NATA accredited for these tests.
 ~ = Indicates an estimated value.

- Analysis as per AS3580.10.1-2016. Samples passed through a 1mm sieve prior to analysis. NATA accreditation does not apply for results reported in g/m².mth as sampling data was provided by the client.
- Sample exposure period is 27 days which is outside the typical exposure period of 30 +/- 2 days as per AS3580.10.1.

Analytical Results

Sub-Matrix: **DEPOSITIONAL DUST**
 (Matrix: **AIR**)

Client sample ID

				COLLINS 1 31/05/19 - 27/06/19	COLLINS 2 31/05/19 - 27/06/19	COLLINS 3 31/05/19 - 27/06/19	----	----
Client sampling date / time				27-Jun-2019 08:00	27-Jun-2019 08:00	27-Jun-2019 08:00	----	----
Compound	CAS Number	LOR	Unit	EN1904441-001	EN1904441-002	EN1904441-003	-----	-----
				Result	Result	Result	----	----
EA141: Total Insoluble Matter								
Total Insoluble Matter	----	0.1	g/m ² .month	0.7	1.3	1.1	----	----
Total Insoluble Matter (mg)	----	1	mg	11	21	17	----	----

Period	TIM (g/m2/month)			Notes	Controls Implemented
	MS 1	MS 2	MS 3		
Feb-13	1.2	1.5	0.5	Introduction of Station 3	
Mar-13	0.6	1.1	2		
Apr-13	1.6	1.5	3.1*	*TIM exceedance	*Measured Ash Content
May-13	0.4	0.8	1.8		
Jun-13	0.7	1.3	1.7		
Jul-13	0.4	0.5	1.3		
Aug-13	0.4	0.2	0.4		
Sep-13	0.5	1.4	0.8		
Oct-13	0.7	1.2	1.1		
Nov-13	0.1	0.3	0.1		
Dec-13	1.7	1.1	1.2		
Jan-14	0.7	0.9	1		
Feb-14	0.8	1.9	0.7		
Mar-14	0.7	1.4	1.8		
Apr-14	0.4	2.1	0.6		
May-14	1.2	1.1	1.2	Cheyne Hudson takes over sampling and reporting	Mesh screens inserted to filter organic content
Jun-14	0.1	0.1	0.1		
Jul-14	0.4	0.4	0.8		
Aug-14	2	2*	**	*Funnel in jug smashed **Jug smashed.	
Sep-14	2.1	0.6	1.5		
Oct-14	1.8	0.9	1.6		
Nov-14	1.5	2.8	6.2*	*Site clean-up and mow on adjacent rental property	
Dec-14	2.2	2.2	1.6		
Jan-15	1.2	1.2	2		
Feb-15	1.7	0.9	2.3		
Mar-15	2.9	3.3	3.6		
Apr-15	6*	1.6	4.4	*New earthworks noted 50 metres from M1	*Monitor results May-15 due to new E1 extraction
May-15	1.5	0.9	0.9		
Jun-15	1.6	1.2	2.0		
Jul-15	1.9	0.8	1.5		
Aug-15	4.2*	1.1	2.5	*Expanded quarry area to within 20 m of M1.	*Relocation of Monitoring Sites 1 and 2 (September)
Sep-15	1.7	0.9	6.1*	*Expansion of nearby Spring Farm urban	*Regular inspection monitor urban development activity
Oct-15	3.9	4	6.4*	*Hot windy weather and nearby grass mowing	*Dust suppression irrigation
Nov-15	1.7	0.5	2.4		
Dec-15	3.5	2.4	5.3*	development	*Regular inspection monitor urban development activity
Jan-16	2	1	4.7*	*Expansion of nearby Spring Farm urban	*Regular inspection monitor urban development activity
Feb-16	1.5	1.1	1.9		
Mar-16	3.3	2.5	2.5		
Apr-16	1.2	1.8	2		
May-16	0.9	1.5	1.6		
Jun-16	2.7	3.6	3.2		
Jul-16	0.9	0.8	4		
Aug-16	0.5	3.3	0.8		
Sep-16	1.0	2.3	1.6		
Oct-16	1.2	0.7	1.8		
Nov-16	1.0	0.8	2.8		
Dec-16	1.6	2.6	11*	*Springs Road widening and very hot dry weather	
Jan-17	1.3	1.3	2.9		
Feb-17	1.0	0.9	2.1		
Mar-17	2.7	1.5	1.8		
Apr-17	0.6	0.4	2.9		
May-17	0.7	0.5	1.8		
Jun-17	1.2	0.6	1.3		
Jul-17	0.8	1.2	1.5		
Aug-17	0.3	1.3	2.2		
Set - 17	1.0	1.6	4.3	High vegetable (leaves)and organic (bugs) content in all samples	
Oct-17	1.7	2.8	2.2		
Nov-17	0.9	1.5	4.6	High vegetable (leaves)and organic (bugs) content in all samples	
Dec-17	0.6	1.2	2.3		
Jan-18	1.3	2.0	2.8		
Feb-18	0.5	1.9	5.6	Very hot and dry month	
Mar-18	0.6	0.7	7.2	Very hot and dry month and at times windy	
Apr-18	6.7	1.1	2.6	MS-1 sample polluted - bird droppings?	
May-18	0.4	0.6	2.5		
Jun-18	0.5	0.5	34.1	MS-1 sample highly polluted - anomalous result	
Jul-18	0.4	0.8	0.7		
Aug-18	0.6	0.9	0.7		
Sep-18	1.0	0.8	1.5		
Oct-18	0.7	1.2	1.4		
Nov-18	0.5	1.0	1.8		
Dec-18	2.4	0.7	2.0		
Jan-19	1.6	3.5	4.7	Very hot and dry month and at times windy	
Feb-19	1.0	2.5	3.6		
Mar-19	2.0	4.3	1.6	No significant activities noted	
Apr-19	0.7	3.2	1.2		
May-19	0.5	1.9	1.4	Fresh road works around Stations 2 and 3	
Jun-19	0.7	1.3	1.1		

APPENDIX 3: Laboratory Quality Control Documentation

QUALITY CONTROL REPORT

Work Order	: ES1919917	Page	: 1 of 3
Client	: HARVEST SCIENTIFIC SERVICES	Laboratory	: Environmental Division Sydney
Contact	: MR MART RAMPE	Contact	: Customer Services ES
Address	: PO BOX 427	Address	: 277-289 Woodpark Road Smithfield NSW Australia 2164
	NARELLAN NSW, AUSTRALIA 2567		
Telephone	: +61 02 4647 6177	Telephone	: +61-2-8784 8555
Project	: COLLINS SPRING FARM	Date Samples Received	: 27-Jun-2019
Order number	: 2019-7	Date Analysis Commenced	: 28-Jun-2019
C-O-C number	: ----	Issue Date	: 30-Jun-2019
Sampler	: MR		
Site	: ----		
Quote number	: EN/222		
No. of samples received	: 1		
No. of samples analysed	: 1		



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Ashesh Patel	Senior Chemist	Sydney Inorganics, Smithfield, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis. Where the LOR of a reported result differs from standard LOR, this may be due to high

Key :
 Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot
 CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
 LOR = Limit of reporting
 RPD = Relative Percentage Difference
 # = Indicates failed QC

Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR: No Limit; Result between 10 and 20 times LOR: 0% - 50%; Result > 20 times LOR: 0% - 20%.

Sub-Matrix: **WATER**

				Laboratory Duplicate (DUP) Report					
<i>Laboratory sample ID</i>	<i>Client sample ID</i>	<i>Method: Compound</i>	<i>CAS Number</i>	<i>LOR</i>	<i>Unit</i>	<i>Original Result</i>	<i>Duplicate Result</i>	<i>RPD (%)</i>	<i>Recovery Limits (%)</i>
EA005P: pH by PC Titrator (QC Lot: 2435378)									
ES1919917-001	COLLINS GW-1	EA005-P: pH Value	----	0.01	pH Unit	5.85	6.07	3.69	0% - 20%
EA010P: Conductivity by PC Titrator (QC Lot: 2435379)									
ES1919917-001	COLLINS GW-1	EA010-P: Electrical Conductivity @ 25°C	----	1	µS/cm	288	288	0.00	0% - 20%



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Spike (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: **WATER**

Sub-Matrix: WATER				Method Blank (MB) Report	Laboratory Control Spike (LCS) Report			
					Spike	Spike Recovery (%)	Recovery Limits (%)	
Method: Compound	CAS Number	LOR	Unit		Result	Concentration	LCS	Low
EA005P: pH by PC Titrator (QCLot: 2435378)								
EA005-P: pH Value	----	----	pH Unit	----	4 pH Unit	99.0	98	102
				----	7 pH Unit	99.6	98	102
EA010P: Conductivity by PC Titrator (QCLot: 2435379)								
EA010-P: Electrical Conductivity @ 25°C	----	1	µS/cm	<1	2100 µS/cm	104	95	113

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

- **No Matrix Spike (MS) or Matrix Spike Duplicate (MSD) Results are required to be reported.**

QA/QC Compliance Assessment to assist with Quality Review

Work Order	: ES1919917	Page	: 1 of 4
Client	: HARVEST SCIENTIFIC SERVICES	Laboratory	: Environmental Division Sydney
Contact	: MR MART RAMPE	Telephone	: +61-2-8784 8555
Project	: COLLINS SPRING FARM	Date Samples Received	: 27-Jun-2019
Site	: ----	Issue Date	: 30-Jun-2019
Sampler	: MR	No. of samples received	: 1
Order number	: 2019-7	No. of samples analysed	: 1

This report is automatically generated by the ALS LIMS through interpretation of the ALS Quality Control Report and several Quality Assurance parameters measured by ALS. This automated reporting highlights any non-conformances, facilitates faster and more accurate data validation and is designed to assist internal expert and external Auditor review. Many components of this report contribute to the overall DQO assessment and reporting for guideline compliance.

Brief method summaries and references are also provided to assist in traceability.

Summary of Outliers

Outliers : Quality Control Samples

This report highlights outliers flagged in the Quality Control (QC) Report.

- **NO** Method Blank value outliers occur.
- **NO** Duplicate outliers occur.
- **NO** Laboratory Control outliers occur.
- **NO** Matrix Spike outliers occur.
- For all regular sample matrices, **NO** surrogate recovery outliers occur.

Outliers : Analysis Holding Time Compliance

- Analysis Holding Time Outliers exist - please see following pages for full details.

Outliers : Frequency of Quality Control Samples

- Quality Control Sample Frequency Outliers exist - please see following pages for full details.



Outliers : Analysis Holding Time Compliance

Matrix: **WATER**

Method	Extraction / Preparation			Analysis		
	Date extracted	Due for extraction	Days overdue	Date analysed	Due for analysis	Days overdue
Container / Client Sample ID(s)						
EA005P: pH by PC Titrator						
Clear Plastic Bottle - Natural COLLINS GW-1	----	----	----	28-Jun-2019	27-Jun-2019	1

Outliers : Frequency of Quality Control Samples

Matrix: **WATER**

Quality Control Sample Type	Count		Rate (%)		Quality Control Specification
	QC	Regular	Actual	Expected	
Laboratory Duplicates (DUP)					
Conductivity by PC Titrator	1	13	7.69	10.00	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	1	19	5.26	10.00	NEPM 2013 B3 & ALS QC Standard

Analysis Holding Time Compliance

If samples are identified below as having been analysed or extracted outside of recommended holding times, this should be taken into consideration when interpreting results.

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times (referencing USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for VOC in soils vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive or Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: **WATER**

Evaluation: ✖ = Holding time breach ; ✔ = Within holding time.

Method	Sample Date	Extraction / Preparation			Analysis		
		Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
Container / Client Sample ID(s)							
EA005P: pH by PC Titrator							
Clear Plastic Bottle - Natural (EA005-P) COLLINS GW-1	27-Jun-2019	----	----	----	28-Jun-2019	27-Jun-2019	✖
EA010P: Conductivity by PC Titrator							
Clear Plastic Bottle - Natural (EA010-P) COLLINS GW-1	27-Jun-2019	----	----	----	28-Jun-2019	25-Jul-2019	✔



Quality Control Parameter Frequency Compliance

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(were) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: **WATER**

Evaluation: ✖ = Quality Control frequency not within specification ; ✔ = Quality Control frequency within specification.

Quality Control Sample Type		Count		Rate (%)			Quality Control Specification
Analytical Methods	Method	QC	Regular	Actual	Expected	Evaluation	
Laboratory Duplicates (DUP)							
Conductivity by PC Titrator	EA010-P	1	13	7.69	10.00	✖	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	EA005-P	1	19	5.26	10.00	✖	NEPM 2013 B3 & ALS QC Standard
Laboratory Control Samples (LCS)							
Conductivity by PC Titrator	EA010-P	1	13	7.69	5.00	✔	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	EA005-P	2	19	10.53	10.00	✔	NEPM 2013 B3 & ALS QC Standard
Method Blanks (MB)							
Conductivity by PC Titrator	EA010-P	1	13	7.69	5.00	✔	NEPM 2013 B3 & ALS QC Standard



Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
pH by PC Titrator	EA005-P	WATER	In house: Referenced to APHA 4500 H+ B. This procedure determines pH of water samples by automated ISE. This method is compliant with NEPM (2013) Schedule B(3)
Conductivity by PC Titrator	EA010-P	WATER	In house: Referenced to APHA 2510 B. This procedure determines conductivity by automated ISE. This method is compliant with NEPM (2013) Schedule B(3)

QUALITY CONTROL REPORT

Work Order	: EN1904441	Page	: 1 of 3
Client	: HARVEST SCIENTIFIC SERVICES	Laboratory	: Environmental Division Newcastle
Contact	: MR MART RAMPE	Contact	:
Address	: PO BOX 427	Address	: 5/585 Maitland Road Mayfield West NSW Australia 2304
	NARELLAN NSW, AUSTRALIA 2567		
Telephone	: +61 02 4647 6177	Telephone	: +61 2 4014 2500
Project	: COLLINS SPRING FARM	Date Samples Received	: 27-Jun-2019
Order number	: 2019-7	Date Analysis Commenced	: 01-Jul-2019
C-O-C number	: ----	Issue Date	: 05-Jul-2019
Sampler	: MR		
Site	: ----		
Quote number	: EN/222		
No. of samples received	: 3		
No. of samples analysed	: 3		



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Dianne Blane	Laboratory Coordinator (2IC)	Newcastle - Inorganics, Mayfield West, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis. Where the LOR of a reported result differs from standard LOR, this may be due to high

Key :
Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot
CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
LOR = Limit of reporting
RPD = Relative Percentage Difference
= Indicates failed QC

Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR: No Limit; Result between 10 and 20 times LOR: 0% - 50%; Result > 20 times LOR: 0% - 20%.

- **No Laboratory Duplicate (DUP) Results are required to be reported.**



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Spike (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

- **No Method Blank (MB) or Laboratory Control Spike (LCS) Results are required to be reported.**

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

- **No Matrix Spike (MS) or Matrix Spike Duplicate (MSD) Results are required to be reported.**
-

QA/QC Compliance Assessment to assist with Quality Review

Work Order	: EN1904441	Page	: 1 of 4
Client	: HARVEST SCIENTIFIC SERVICES	Laboratory	: Environmental Division Newcastle
Contact	: MR MART RAMPE	Telephone	: +61 2 4014 2500
Project	: COLLINS SPRING FARM	Date Samples Received	: 27-Jun-2019
Site	: ----	Issue Date	: 05-Jul-2019
Sampler	: MR	No. of samples received	: 3
Order number	: 2019-7	No. of samples analysed	: 3

This report is automatically generated by the ALS LIMS through interpretation of the ALS Quality Control Report and several Quality Assurance parameters measured by ALS. This automated reporting highlights any non-conformances, facilitates faster and more accurate data validation and is designed to assist internal expert and external Auditor review. Many components of this report contribute to the overall DQO assessment and reporting for guideline compliance.

Brief method summaries and references are also provided to assist in traceability.

Summary of Outliers

Outliers : Quality Control Samples

This report highlights outliers flagged in the Quality Control (QC) Report.

- **NO** Method Blank value outliers occur.
- **NO** Duplicate outliers occur.
- **NO** Laboratory Control outliers occur.
- **NO** Matrix Spike outliers occur.
- For all regular sample matrices, **NO** surrogate recovery outliers occur.

Outliers : Analysis Holding Time Compliance

- **NO** Analysis Holding Time Outliers exist.

Outliers : Frequency of Quality Control Samples

- **NO** Quality Control Sample Frequency Outliers exist.



Analysis Holding Time Compliance

If samples are identified below as having been analysed or extracted outside of recommended holding times, this should be taken into consideration when interpreting results.

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times (referencing USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for VOC in soils vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive or Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: **AIR**

Evaluation: ✖ = Holding time breach ; ✔ = Within holding time.

Method	Sample Date	Extraction / Preparation			Analysis			
Container / Client Sample ID(s)		Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation	
EA141: Total Insoluble Matter								
Dust Gauge - Copper Sulfate (EA141)								
COLLINS 1 - 31/05/19 - 27/06/19, COLLINS 3 - 31/05/19 - 27/06/19	COLLINS 2 - 31/05/19 - 27/06/19,	27-Jun-2019	----	----	----	01-Jul-2019	24-Dec-2019	✔



Quality Control Parameter Frequency Compliance

- No Quality Control data available for this section.



Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
Total Insoluble Matter (TIM)	EA141	AIR	In house: Referenced to AS 3580.10.1. A gravimetric procedure reporting Total Insoluble solids in deposited dust.